

GESCOplus

GAMA HOME

A+
SCOP

A++
SEER

A+++
SCOP
Warmer

3 AÑOS GARANTÍA TOTAL
COMPROMISO DE CALIDAD

21dB
SEGUNDO O MODELO



Ficha técnica

SPLIT 1X1

SERIE SURE



| | | GES26SUREWF | GES35SUREWF | GES52SUREWF | GES71SUREWF | |
|---------------------------|-------------------------------|--------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| MODELOS | IU | GES26SUREWF-I | GES35SUREWF-I | GES52SUREWF-I | GES71SUREWF-I | |
| | OU | GES26SUREWF-O | GES35SUREWF-O | GES52SUREWF-O | GES71SUREWF-O | |
| CÓDIGO EAN | | 8435483850095 | 8435483850125 | 8435483850156 | 8435483850200 | |
| Alimentación eléctrica | V,F,Hz | 220~240V (1 Fase ~ 50Hz) | | | | |
| Conexión | | Unidad exterior | | | | |
| RENDIMIENTO | | | | | | |
| Capacidad refrigeración | Capacidad | kW | 2,6 (0,9 - 3,39) | 3,5 (1,11 - 4,16) | 5,2 (0,34 - 5,83) | 7,1 (2,08 - 7,95) |
| | | Btu/h | 9.000 (3.100~11.600) | 12.000 (3.800~14.200) | 18.000(11.570~19.900) | 24.000(7.100~27.000) |
| | Consumo | W | 732 (100~1.240) | 1.213 (130~1.580) | 1.500(560~2.050) | 2.600(420~3150) |
| | SEER | - | 6,3 | 6,1 | 7,4 | 6,1 |
| | Clasificación energética | Frío | A++ | A++ | A++ | A++ |
| Capacidad calefacción | Capacidad | kW | 2,91 (0,82 - 3,37) | 3,8 (1,08 - 4,22) | 5,56 (3,1 - 5,85) | 7,3 (1,61 - 7,95) |
| | | Btu/h | 10.000 (2.800~11.500) | 13.000 (3.700~14.400) | 19.000 (10.580~19.960) | 25.000 (5.500~27.000) |
| | Consumo | W | 733 (120~1.200) | 1.088 (100~1.680) | 1.570 (780~2.000) | 2.400 (300~2.750) |
| | SCOP | - | 4 | 4 | 4 | 4 |
| | Clasificación energética | Calor | A+ | A+ | A+ | A+ |
| CARACTERÍSTICAS | | | | | | |
| Unidad interior | Potencia sonora | dB(A) | 54 | 55 | 56 | 59 |
| | Presión sonora (H/M/L) | dB(A) | 38,5/32/25/21 | 40,5/34,5/25/22 | 42,5/36/26/25 | 44,5/42/36/28 |
| | Caudal de aire | m³/h | 466/360/325 | 540/430/314 | 840/680/540 | 980/817/662 |
| | Temperatura de operación | °C | 16 ~ 31 | 16 ~ 31 | 16 ~ 31 | 16 ~ 31 |
| Unidad exterior | Potencia sonora | dB(A) | 62 | 63 | 63 | 67 |
| | Presión sonora | dB(A) | 55,5 | 56 | 56 | 59 |
| | Caudal de aire | m³/h | 1.750 | 1.800 | 2.100 | 3.500 |
| | Temperatura de operación | °C | (-15 ~ 50) / (-15 ~ 30) | (-15 ~ 50) / (-15 ~ 30) | (-15 ~ 50) / (-15 ~ 30) | (-15 ~ 50) / (-15 ~ 30) |
| Refrigerante | Compresor | | GMCC | GMCC | GMCC | GMCC |
| | Tipo/Carga | R32/Kg | 0,55 | 0,55 | 1,08 | 1,42 |
| | Carga adicional >5 | g/m | 12 | 12 | 12 | 24 |
| DIMENSIONES Y PESO | | | | | | |
| Unidad interior | Dimensiones netas (An×Al×Pr) | mm | 805x285x194 | 805x285x194 | 957x302x213 | 1040x327x220 |
| | Dimensiones brutas (An×Al×Pr) | mm | 870x365x270 | 870x365x270 | 1035x385x295 | 1120x405x315 |
| | Peso neto / bruto | Kg | 7,6/9,7 | 7,6/9,7 | 10/13 | 12,3/15,8 |
| Unidad exterior | Dimensiones netas (An×Al×Pr) | mm | 720x495x270 | 720x495x270 | 805x554x330 | 890x673x342 |
| | Dimensiones brutas (An×Al×Pr) | mm | 835x540x300 | 835x540x300 | 915x615x370 | 995x740x398 |
| | Peso neto/bruto | Kg | 23,2/25 | 23,2/25 | 32,7/35,4 | 42,9/45,9 |
| CONEXIONES | | | | | | |
| Tubería frigorífica | Líquido - Gas | Pulg. | 1/4" - 3/8" | 1/4" - 3/8" | 1/4" - 1/2" | 3/8" - 5/8" |
| | Longitud máx. | m | 25 | 25 | 30 | 50 |
| | Desnivel máx. | m | 10 | 10 | 20 | 25 |
| Conexiones eléctricas | Alimentación | mm | 2 x 2,5 + T | 2 x 2,5 + T | 2 x 2,5 + T | 2 x 2,5 + T |
| | Interconexión | mm | 4 x 2,5 + T | 4 x 2,5 + T | 4 x 2,5 + T | 4 x 2,5 + T |